

DS-7604/7608NI-SE/(8)P Embedded NVR




DS-7600NI-SE/P



Key features


- Up to 8 Integrated PoE Network Interfaces
- Up to 5 Megapixels Resolution Recording
- Up to 8-ch synchronous playback at 4CIF resolution.

Rear Panel of DS-7604NI-SE/P



1. LAN Network Interface
2. RS-485 Interface
3. 100~240VAC Power Input
4. Power Switch
5. USB Interface
6. GND
7. HDMI Interface
8. VGA Output
9. Audio In
10. Audio Out
11. Network Interfaces with PoE function
12. Alarm In / Out

Rear Panel of DS-7608NI-SE/8P



1. LAN Network Interface
2. RS-485 Interface
3. 100~240VAC Power Input
4. Power Switch
5. USB Interface
6. GND
7. HDMI Interface
8. VGA Output
9. Audio In
10. Audio Out
11. Network Interfaces with PoE function
12. Alarm In / Out

Specifications

	DS-7604NI-SE/P	DS-7608NI-SE/8P
Video / Audio input		
IP Video input	4-ch	8-ch
Audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)	
Video/Audio output		
Decoding resolution	5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF	
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz	
Audio output	1-ch, RCA (Linear, 1kΩ)	
Playback resolution	5MP /3MP /1080P /UXGA /720P /VGA /4CIF /DCIF /2CIF /CIF /QCIF	
Synchronous playback	4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP	8-ch, 4CIF / 4-ch, 720P / 2-ch, 1080P / 1-ch, 5MP
Hard disk		
Type	2 SATA interfaces for 2 HDDs	
Capacity	Up to 4TB capacity for each disk	
External interface		
Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface 4 independent 10 /100 Mbps PoE Ethernet interfaces	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface 8 independent 10 /100 Mbps PoE Ethernet interfaces
Input	20 Mbps	40 Mbps
Output	60 Mbps	80 Mbps
Serial interface	1 RS-485 half-duplex interface	
USB interface	2 x USB2.0	
Alarm in	4	
Alarm out	1	
General		
Power supply	100~240VAC, 47~63Hz, 3A	
Power Consumption	67W (including 4-port PoE)	145W (including 8-port PoE)
Working temperature	-10 °C~ +55 °C	
Working humidity	10%~90%	
Chassis	19-inch rack mounted 1U chassis	
Dimensions (W x D x H)	445 × 290 × 45 mm	
Weight	≤ 2.5Kg (without HDD or DVD-R/W)	